



SPECIFICATION

FPG 15000SE/STE

Model	FPG15000SE	FPG15000STE
AC Frequency	50HZ/60HZ	50HZ/60HZ
Rated AC Voltage	220V / 120/240V	220/380V / 230/400V
Rated AC Current	45.5A / 45.8A	18.2A / 36.1A
Max. AC Output (5min)	12.0KVA / 13.5KVA	14.5KVA / 15.5KVA
Rated AC Output	10.0KVA / 11.0KVA	12.0KVA / 13.0KVA
Protection Type	IP23	IP23
Alternator Type	Brush,self exciting, synchronous,2-pole	Brush,self exciting, synchronous,2-pole
Voltage Regulator	AVR	AVR
Insulation Level	F	F
Power Factor COS	1	1
Phase	Single phase	3 phase
Engine Brand	SUBARU	SUBARU
Engine Model or P/N	EH72-2	EH72-2
Engine Type	Air cooling,4-stroke, V-twin cylinder,OHV	Air cooling,4-stroke, V-twin cylinder,OHV
Bore x stroke (mm)	84 x 65	84 x 65
Cylinder	2	2
Cylinder order	V-twin	V-twin
Displacement (CC)	720	720

Maximum Power Output (HP/ KW)	25HP/3600rpm	25HP/3600rpm
Ignition System	Flywheel magneto	Flywheel magneto
Starting System	Electric	Electric
Fuel	Unleaded automobile gasoline	Unleaded automobile gasoline
Fuel Tank Capacity	40.0L (FULL 42L)	40.0L (FULL 42L)
Oil Capacity	1.55L	1.55L
Soundpressure Level @ 7	79dB(A) / 82dB(A)	79dB(A) / 82dB(A)
Dimension (L x W x H)4''wheel	910X650X846(4''wheel)	910X650X846(4''wheel)
Dry Weight (including 4''wheel) (appr.)	170	170
Gross Weight (appr.)	186(4''wheel)	186(4''wheel)
Packing size (LxWxH)	940x675x860	940x675x860
Package artwork	Kraft corrugated carton + pallet	Kraft corrugated carton + pallet
4-wheel transport kit	STD	STD
2-wheel transport kit	OPTIONAL	OPTIONAL
AC Plug	STD	STD
AC Cord Set	OPTIONAL	OPTIONAL
DC Charging Cord	NO	NO
Oil bottle	OPTIONAL	OPTIONAL
Funnel	STD	STD
Accessory Tool kit	STD	STD

Inquiries: 08033053993, 08053317814 & 08023023081

Click to open [Our website](#)